



RECHARGEABLE



Εισαγωγή διάθεση:  **MOTUS**



VRLA

TYPE	VOLT	ΑΗ(20Η)	ΔΙΑΣΤΑΣΕΙΣ			Σ.Υ.	ΣΥΝΙΣΤΡ. ΦΟΡΤ.	ΜΕΓ.Ρ. ΕΚΦ.5"	ΒΑΡΟΣ KG
			Μκ.	Πλ.	Υψ.				
1-6	12	41	51	42	51	58	0,30	15	0,28
1.2-6	12	1,2	97	24	52	59	0,24	18	0,30
3.4-6	12	3,4	134	34	60	67	0,68	51	0,70
4.5-6	12	4,5	70	47	101	106	0,90	68	0,85
5-6	12	5	70	47	101	106	1,00	75	0,89
7.2-6	12	7,2	151	34	94	100	1,40	108	1,25
8.5-6	12	8,5	98	56	118	118	1,70	128	1,60
12-6	12	12	151	50	95	101	2,40	180	1,78
3.2-8	12	3,2	134	37	64	70	0,64	48	0,86
0.8-12	12	0,8	96	25	61	61	0,16	12	0,38
1.3-12	12	1,3	97	43	52	59	0,24	20	0,60
2.2-12	12	2,2	178	35	60	67	0,44	33	0,90
2.3-12	12	2,3	178	35	60	67	0,46	35	0,96
2.3-12B	12	2,3	182	24	61	61	0,40	35	0,78
2.9-12	12	2,9	79	56	99	105	0,58	44	1,21
3.4-12	12	3,4	134	67	60	67	0,68	51	1,42
4.5-12	12	4,5	90	70	101	107	0,90	68	1,72
5-12	12	5	151	50	94	100	1,00	75	1,80



TYPE	VOLT	ΑΗ(20Η)	ΔΙΑΣΤΑΣΕΙΣ Μκ. Πλ. Υψ.			Σ.Υ.	ΣΥΝΙΣΤΡ. ΦΟΡΤ.	ΜΕΓ.Ρ. ΕΚΦ.5"	ΒΑΡΟΣ KG
5-12B	12	5	90	70	101	107	1,00	75	1,76
7-12	12	7	151	65	94	100	1,40	105	2,00
7.2-12	12	7,2	151	65	94	100	1,44	108	2,40
8.5-12	12	8,5	151	65	94	100	1,70	128	2,55
12-12	12	12	151	98	95	100	2,40	180	3,50
18-12	12	18	181	76	167	167	3,60	270	5,85
25-12	12	25	166	175	125	125	5,00	375	9,00
28-12	12	28	165	125	175	175	5,60	420	9,80
33-12	12	33	196	130	158	163	6,60	495	11,95
40-12	12	40	196	165	170	170	8,00	600	13,55
55-12	12	55	229	138	208	212	11,00	825	18,50
70-12	12	70	350	166	174	174	13,00	1050	22,70
80-12	12	80	260	168	208	212	16,00	1200	25,85
100-12	12	100	329	173	214	221	20,00	1500	32,40
120-12	12	120	407	173	210	235	24,00	1800	38,40
150-12	12	150	483	170	240	240	30,00	2250	44,50
200-12	12	200	530	209	214	218	40,00	3000	60,00