





ELIX ULTRA X	TECHNICAL DATASHEET	Created:	9.12.2023
		Modified:	5.3.2024
TYPE	BCI 31		
CODE	U-1200LA		



PERFORMANCES

Voltage (V):	12
C20(Ah):	120
Cold Cranking Ampere (A):	920 EN
Charge Acceptance (A):	12
Plates per Cell (pcs):	20
Pos./ Grid Alloy:	Exp. / Pb-Ca-Sn
Neg./ Grid Alloy:	Exp. / Pb-Ca
Separator:	PE(Enveloped)

WEIGHT & DIMENSIONS (max.)

Battery Weight (kg):	26 (+/-2%) with acid
Lead Weight (kg):	13,266
Length (mm):	330
Width (mm):	173
Height (mm):	217
Total Height (mm) :	240

CONTAINER

Type:	BCI 31 Acc. To BCI
Hold Down:	No
H.D.Adapter:	No

COVER

Type:	
Polarity:	(-, +) Cell layout
Terminal Adapter:	No
Magic Eye:	Yes
Degassing system	Yes
Flame Arrestor	Yes 2pcs(filter)

PLUGS

Type:	No Vent Sealed
-------	----------------

HANDLE

Type:	Yes
-------	-----

OTHERS

Degassing Tube:	No
-----------------	----