





ELIX ULTRA X	TECHNICAL DATASHEET	Created:	9.12.2023
		Modified:	5.3.2024
TYPE	DIN C		
CODE	U-70021		



PERFORMANCES

Voltage (V):	12
C20(Ah):	200
Cold Cranking Ampere (A):	1200 SAE
Charge Acceptance (A):	20
Plates per Cell (pcs):	32
Pos./ Grid Alloy:	Exp. / Pb-Ca-Sn
Neg./ Grid Alloy:	Exp. / Pb-Ca
Separator:	PE(Enveloped)

WEIGHT & DIMENSIONS (max.)

Battery Weight (kg):	50,8(+/-2%) with acid
Lead Weight (kg):	25,634
Length (mm):	518
Width (mm):	276
Height (mm):	216
Total Height (mm) :	239

CONTAINER

Type:	DIN C
Hold Down:	No
H.D.Adapter:	No

COVER

Type:	Flat/Seald -
Polarity:	(+, -) Cell layout
Terminal Adapter:	No
Magic Eye:	Yes
Degassing system	Yes
Flame Arrestor	Yes

PLUGS

Type:	No Vent Sealed
-------	----------------

HANDLE

Type:	Yes 2x Rope
-------	-------------

OTHERS

Degassing Tube:	No
-----------------	----