





ELIX EFB START&STOP	TECHNICAL DATASHEET	Created:	31.01.2024
		Modified:	5.3.2024
TYPE	LN3		
CODE	EFB-57020-S		



PERFORMANCES

Voltage (V):	0
C20(Ah):	70
Cold Cranking Ampere (A):	680 EN
Charge Acceptance (A):	14
Plates per Cell (pcs):	15
Pos./ Grid Alloy:	Exp. / Pb-Ca-Sn
Neg./ Grid Alloy:	Exp. / Pb-Ca
Separator:	PE(Enveloped)

WEIGHT & DIMENSIONS (max.)

Battery Weight (kg):	18,5 (+/-2%) with acid
Lead Weight (kg):	12,1 base on ingot
Length (mm):	277
Width (mm):	174
Height (mm):	188
Total Height (mm) :	188

CONTAINER

Type:	LN3 Acc. To EN
Hold Down:	B3
H.D.Adapter:	No

COVER

Type:	Flat/sealed type -
Polarity:	(-,+) Cell layout
Terminal Adapter:	No
Magic Eye:	Yes
Degassing system	Short side
Flame Arrestor	Yes 2pcs

PLUGS

Type:	No
-------	----

HANDLE

Type:	2x intergated -
-------	-----------------

OTHERS

Degassing Tube:	No
-----------------	----